



The palm grip B 5 is an actuating element for our multi-axis and single-axis controller. It can also be used as an actuating element for hydraulic drives. Push buttons, rocker switches, e.t.c., can also be fitted to suit appropriate requirements.

The palm grip has a highly flexible cable 4 (8) x 0,25 mm² x 450 mm long.

The mounting piece for the drive rod can be supplied with a tapped hole M 8 or M 10 (standard = M 10).

The palm grip B 5 is made of PA plastic and is black in colour.

Contact complement **2 A 250 V AC 15 / 3 A 24 V DC 13**
or **0,5 A 250 V AC 15 / 1,5 A 24 V DC 13**

Micro change over contacts

Permissible ambient temperature

Operating -40°C to +60°C
Storage -50°C to +80°C

Climate resistance

Damp heat constant

Damp heat cyclic

Degree of protection front

IEC 60068-2-78
IEC 60068-2-30
IP 54 IEC/EN 60529

Pos.				Contact-complement	Weight gramm	Type	Price EURO
1		without built in		KBAD / 254		B 5	
2		Rocker switch top tip-0-tip	T-0-T installed Pos. 1	KBAD / 248	2 change over contact 3 A 24 V DC 13	B 5 W	
3		Rocker switch top tip-0-rest	T-0-R installed Pos. 1				
4		Rocker switch top rest-0-rest	R-0-R installed Pos. 1				
5		Rocker switch top tip-0-tip with push button side	T-0-T installed Pos. 1 installed Pos. 2	KBAD / 294	2 change over contact 3 A 24 V AC 13 1 change over contact 1,5A 24 V DC 13	B 5 WD	
7		Push button top mechanical operation	installed Pos. 1	KBAD / 311 KBAD / 250	1 change over contact 1,5A 24 V DC 13	B 5 T B 5 D	
8		Push button top	installed Pos. 1				
9		Push button top with 1 push button side	installed Pos. 1 installed Pos. 2	KBAD / 252	2 change over contact 1,5A 24 V DC 13	B 5 2D	
11		1 push button side	installed Pos. 1	KBAD / 246	change over contact 1,5A 24 V DC 13	B 5 D B 5 2D	
12		2 push button side	installed Pos. 2				
21		Cable 4 or 8 x 0,25 mm ² x 450 mm long					
22		wired included in Pos. 1-12					
		Additional price per metre cable 4-pole					
		Additional price per metre cable 8-pole					